


# SPHERICAL ROLLER BEARINGS



CHINA HOSIN



With the same center as the bearing, the spherically formed outer ring raceway can make self-alignment. Their rolling elements linearly come into contact with the raceways of inner ring and outer ring. The bearings can take great radial load, suitable for heavy machinery used in mining, metallurgical, paper-making and construction. DH could make 20000 series C, CC, CA, K, W33 type spherical roller bearings.

Type	d	D	B	weight(kg)	Type	d	D	B	weight(kg)
22205	25	52	18	0.16	22334	170	360	120	57.9
22206	30	62	20	0.26	22336	180	380	126	67.5
22207	35	72	23	0.39	22338	190	400	132	78.1
22208	40	80	23	0.48	23022	110	170	45	3.75
22209	45	85	23	0.53	23024	120	180	46	4.11
22210	50	90	23	0.57	23026	130	200	52	5.99
22211	55	100	25	0.76	23028	140	210	53	6.52
22212	60	110	28	1.04	23030	150	225	56	7.9
22213	65	120	31	1.43	23032	160	240	60	9.66
22214	70	125	31	1.51	23034	170	260	67	13
22215	75	130	31	1.59	23036	180	280	74	17.1
22216	80	140	33	1.93	23038	190	290	75	17.6
22217	85	150	36	2.41	23040	200	310	82	22.4
22218	90	160	40	3.11	23122	110	180	56	5.7
22219	95	170	43	3.82	23124	120	200	62	7.84
22220	100	180	46	4.62	23126	130	210	64	8.68
22222	110	200	53	6.78	23128	140	225	68	10.5
22224	120	215	58	8.45	23130	150	250	80	15.8
22226	130	230	64	10.5	23132	160	270	86	20.3
22228	140	250	68	14.5	23134	170	280	88	21.8
22230	150	270	73	18.4	23136	180	300	96	27.5
22232	160	290	80	23.2	23138	190	320	104	34.5
22234	170	310	86	28.9	23140	200	340	112	42.6
22236	180	320	86	30.2	23218	90	160	52.4	4.52
22238	190	340	92	35.5	23220	100	180	60.3	6.6
22240	200	360	98	42.7	23222	110	200	69.8	9.54
22308	40	90	33	0.96	23224	120	215	76	12.1
22309	45	100	36	1.28	23226	130	230	80	14.3
22310	50	110	40	1.67	23228	140	250	88	18.8
22311	55	120	43	2.19	23230	150	270	96	24.2
22312	60	130	46	2.72	23232	160	290	104	30.5
22313	65	140	48	3.34	23234	170	310	110	36.4
22314	70	150	51	4.04	23236	180	320	112	38.9
22315	75	160	55	4.96	23238	190	340	120	47.6
22316	80	170	58	5.91	23240	200	360	128	57.1
22317	85	180	60	6.72	24024	120	180	60	5.33
22318	90	190	64	8.06	24026	130	200	69	7.84
22319	95	200	67	9.3	24028	140	210	69	8.37
22320	100	215	73	12.2	24030	150	225	75	10.5
22322	110	240	80	17	24032	160	240	80	12.7
22324	120	260	86	22.2	24034	170	260	90	17
22326	130	280	93	27.4	24036	180	280	100	22.7
22328	140	300	102	34.3	24038	190	290	100	23.9
22330	150	320	108	41.7	24040	200	310	109	30.4
22332	160	340	114	49.5					