

# AUTO FRONT WHEEL BEARINGS



CHINA HOSIN



1. Since the bearing is designed to have the appropriate internal axial clearance, there is no need for pre-load addition adjustment (dimensional adjustment for spacers), which is necessary for singly row bearing assembly.
2. Greasing.
3. An appropriate amount of high-grade grease (excellent for hear 130degree and wear resistant) is pre packed in the bearings.
4. Sealed type bearings are mud-proof, dust-proof, and leak-proof (grease) all without the use of shaft seals.
5. High refining bearing steel can be used or the bearing, thereby extending its service life.

Bearing No.	Dimension(mm)				Mass	Seal	Remarks
	d	D	B	C			
DAC25520037	25	52	37	37	0.31	D	⊙
DAC25520043	25	52	43	43	0.36	D	⊙
DAC25550043	25	55	43	43	0.41	D	⊙
DAC28580042	28	58	42	42	0.44	A、D	⊙
DAC28610042	28	61	42	42	0.5	E	
DAC30500020	30	50	20	20	0.08	D	
DAC30540024	30	54	24	24	0.1	D	⊙
DAC30550030/25	30	55	30	25	0.2	E	
DAC30600037	30	60	37	37	0.42	D	
DAC30600337	30		37	37	0.42	D	
DAC30620032	30	62	32	32	0.4	D	
DAC30640042	30	64	42	42	0.49	D	⊙
DAC32720045	32	72	45	45	0.6	E	
DAC34620037	34	62	37	37	0.41	D	⊙
DAC34640037	34	64	37	37	0.43	C	⊙
DAC34660037	34	66	37	37	0.5	C	⊙
DAC35640037	35	64	37	37	0.41	C	⊙
DAC35650035	35	65	35	35	0.4	A、B、D、F	⊙
DAC35660033	35	66	33	33	0.43	D	⊙
DAC35660037	35	66	37	37	0.48	A、C	⊙
DAC35680037	35	68	37	37	0.52	A、B、C	⊙
DAC35680233/30	35		33	30	0.47	E	⊙
DAC35720033	35	72	33	33	0.58	A、B	⊙
DAC35720034	35	72	34	34	0.58	A、B	
DAC35720233/31	35		33	31	0.55	E	⊙
DAC36680033	36	68	33	33	0.47	D、E	
DAC37720037	37	72	37	37	0.59	A、B、C	⊙
DAC37720237	37		37	37	0.59	A、B、C	⊙
DAC37720437	37		37	37	0.59	A、B、C	⊙
DAC37740045	37	74	45	45	0.79	D	
DAC38700037	38	70	37	37	0.54	A、B	⊙
DAC38700038	38	70	38	38	0.55	A、B	⊙
DAC38710033/30	38	71	33	30	0.52	E	
DAC38710039	38	71	39	39	0.56	D	⊙
DAC38720040	38	72	40	40	0.57	D	
DAC38720236/33	37.99		36	33	0.54	E	
DAC38730040	38	73	40	40	0.62	D	
DAC38740036/33	38	74	36	33	0.58	E	▲